

## DESCRIPTION

- A-Component is an aromatic polymeric isocyanate resin [diphenylmethane-diisocyanate or p-MDI]

## RECOMMENDED USES

- A-Component is used in conjunction with Liquifoam B-Component resins to create various polyurethane foams. It is blended in a 1:1 ration with B component resins.

Property	Test Method	Result
Color Visual		Brown Liquid
Solids, weight %		100
Specific Gravity @ 25° F		1.24
Viscosity @ 25° C, mPa.s		150 - 250
Weight Per Gallon, @ 25° F		10.3
NCO Content, minimum %		31.0 Minimum
Acidity, %		0.01 - 0.03 Max

## SHELF LIFE

When stored in the original unopened container at 55° F - 75° F, the shelf life on the components is a minimum of six months.

## SAFETY PRECAUTIONS

Dermal exposure to the isocyanate component "A" may cause sensitization, especially if chronic exposure is encountered. Skin contact with the material should be flushed immediately with copious amounts of water followed by 30% Isopropyl alcohol solution.

## PACKAGING/SHIPPING INFORMATION

### CONTAINER SIZE

15 Gallon drum  
55 Gallon drum  
275 Gallon Tote

### SHIPPING CLASS

Class 55  
Class 55  
Class 55